

# ELECTRIC DRYER MODELS: Features & Specs



E-2408

Product no. 58013

<b>ELECTRIC DRYER MODELS</b>	<b>E-2408</b>
<b>product item number</b>	<b>58013</b>
<b>Features/Specs.</b>	
Service Voltage	208-240V
Amps per phase	30 Amps 1-Phase 1 Phase only
KW / BTU @ 220 Volts	5.4 KW / 18,300 BTU
Power Cord Supplied?	Optional
Unit Length Total	8' (243cm)
Unit Width Total (body + control panel)	32" + 5" (81cm + 13cm)
Unit Height Total	47" (119cm)
Belt Width	24" (61cm)
Oven Length	42" (107cm)
Conveyor Entrance Length	20" (51cm)
Conveyor Exit Length	20" (51cm)
Fume Hood	6" each end
Oven Throat / Door Openings	6" Adjustable
Belt Speed Control	Analog 0-10
Belt Type	Fiberglass TCF
Conveyor Pulleys	Flat
Belt Motor Outlets	N/A
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Analog - Omron E5C2
Number of Temp Control Zones	1 Zone
High / Low Temp Alarm?	No
Relay Lights	No
Heater Lights	No
Heater Overload Protection	Main Breaker
Control Overload Protection	P&B W28 Series
Main Power Breaker or Contactor	Breaker
Number of Heaters	2 - 12x24" 18 Ohm
Recirculating Airflow	None
Number of Recirculating Air Zones	N/A
Recirculating Airflow speed	N/A
Exhaust Duct Size	10"
Exhaust CFM @ 60 Hz	300 CFM
Exhaust Motor / Blade	3M534 & 4C475
Chimney None/Fixed/Variable	None
Backdraft Flapper?	No
Wheels on Legs	No
Insulation under top skin	No
Certifications ETL/CE/CSA	None
<b>PRODUCTION CAPACITY PER HOUR</b>  (prints of 38 x 38cm occupying belt space of about 50 x 50cm, for 90 seconds and 60 seconds curing time - IN UNITS)	104-156
Shipping Weight (in kg and lbs)	208 kg - 459 lbs
Shipping size (in cm)	229 x 94 x 92 cm
Shipping size (in inches)	90 x 37 x 36"