

ELECTRIC DRYER MODELS: Features & Specs



E-2255

Product no. 33026

ELECTRIC DRYER MODELS		E-2255
product item number		33026
Features/Specs.		
Service Voltage		110-120V
Amps per phase		18.5 Amp 1-Ph 120V 1 Phase Only
KW / BTU @ 220 Volts		2.2 KW / 7,500 BTU
Power Cord Supplied?		Optional
Unit Length Total		5.5' (165cm)
Unit Width Total (body + control panel)		30" + 5" (76cm + 13cm)
Unit Height Total		47" (119cm)
Belt Width		22" (56cm)
Oven Length		26" (66cm)
Conveyor Entrance Length		17.5" (44cm)
Conveyor Exit Length		17.5" (44cm)
Fume Hood		None
Oven Throat / Door Openings		5" Fixed
Belt Speed Control		Analog 0-9
Belt Type		Fiberglass TCF
Conveyor Pulleys		Flat
Belt Motor Outlets		N/A
Belt Direction Facing Control Box		Right to Left
Temperature Control - Type		Digital
Number of Temp Control Zones		0 Zone
High / Low Temp Alarm?		No
Relay Lights		No
Heater Lights		No
Heater Overload Protection		Main Breaker
Control Overload Protection		P&B W28 Series
Main Power Breaker or Contactor		Breaker
Number of Heaters		
Recirculating Airflow		None
Number of Recirculating Air Zones		N/A
Recirculating Airflow speed		N/A
Exhaust Duct Size		3"
Exhaust CFM @ 60 Hz		
Exhaust Motor / Blade		
Chimney None/Fixed/Variable		None
Backdraft Flapper?		No
Wheels on Legs		No
Insulation under top skin		No
Certifications ETL/CE/CSA		None
PRODUCTION CAPACITY PER HOUR (prints of 38 x 38cm occupying belt space of about 50 x 50cm, for 90 seconds and 60 seconds curing time - IN UNITS)		70 - 105
Shipping Weight (in kg and lbs)		140 kg - 310 lbs
Shipping size (in cm)		178 x 91 x 76 cm
Shipping size (in inches)		70 x 36 x 30"