

ELECTRIC DRYER MODELS: Features & Specs



EA-2410

Product no. 58022

ELECTRIC DRYER MODELS	EA-2410
product item number	58022
Features/Specs.	
Service Voltage	208-240V
Amps per phase	35 Amps 1-Phase 1 Phase Only
KW / BTU @ 220 Volts	6.0 KW / 20,630 BTU
Power Cord Supplied?	Optional
Unit Length Total	10 Feet
Oven Length	60 Inches
Conveyor Entrance Length	24 Inches
Conveyor Exit Length	24 Inches
Fume Hood	6" each end
Oven Throat / Door Openings	4" Fixed
Belt Speed Control	Analog 0-10
Belt Type	Fiberglass TCF
Conveyor Pulleys	Flat
Belt Motor Outlets	N/A
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Analog - Omron E5C2
Number of Temp Control Zones	1 Zone
High / Low Temp Alarm?	No
Relay Lights	No
Heater Lights	No
Heater Overload Protection	Main Breaker
Control Overload Protection	P&B W28 Series
Main Power Breaker or Contactor	Breaker
Number of Heaters	2 - 12x24 16 Ohm
Mixing Airflow	Yes - Fixed 1-Speed
Exhaust Duct Size	10"
Exhaust CFM @ 60 Hz	300 CFM
Exhaust Motor / Blade	3M534 & 4C475
Chimney None/Fixed/Variable	Fixed
Backdraft Flapper?	No
Wheels on Legs	No
Insulation under top skin	No
Certifications ETL/CE/CSA	None
PRODUCTION CAPACITY PER HOUR (prints of 38 x 38cm occupying belt space of about 50 x 50cm, for 90 seconds and 60 seconds curing time - IN UNITS)	149 - 223
Shipping Weight (in kg and lbs)	206 kg - 701 lbs
Shipping size (in cm)	330 x 122 x 100 cm
Shipping size (in inches)	130 x 48 x 39"