

ELECTRIC DRYER MODELS: Features & Specs



SubliPro
2414

Product no. 71054

ELECTRIC DRYER MODELS		SubliPro 2414 9" Opening 208V
product item number		71054
Features/Specs.		
Service Voltage		208V 3-Ph
Amps per phase		50 Amps 3-Ph
		3-Phase Only
KW / BTU input		15.0 KW / 51,150 BTU
Unit Length Total		14' (427cm)
Unit Width Total		32" (81cm)
Oven Unit Height Total - To top of exhaust		67-1/2" (171.5cm)
Cooler Unit Height Total		74.25" (188.6cm)
Belt Width		24" (61cm)
Oven Length		60 Inches
"Dead" conveyor space between oven and cooler		12" (30.5cm)
Conveyor Entrance Length		24 Inches
Conveyor Exit Length		24 Inches
Fume Hood		6" each end
Oven Throat / Door Openings		9" With Curtains
Belt Speed Control		Digital
Belt Type		Stainless Steel
Belt Direction Facing Control Box		Right to Left
Temperature Control - Type		Digital - West 6100
Number of Temp Control Zones		1 Zone
Relay Lights		Yes - 3
Heater Lights		Yes - 6
Recirculating Airflow		Yes - Variable
Number of Recirculating Air Zones		1 Zone
Recirculating Airflow speed		1500 CFM
Exhaust Duct Size		8"
Exhaust CFM @ 60 Hz		350 CFM
Cooler Section		Yes
Cooler Length		3' (91cm)
CFM		1550
Wheels on Legs		Yes
Certifications ETL/CE/CSA		None
PRODUCTION CAPACITY PER HOUR Mugs placed on 6" centers down the belt 4 wide on 24" belts, 6 wide on 36" belts and 7 wide on 48" belts with 12 minute retention time inside oven. <i>Note: Actual output will depend on ink requirement of retention time in the oven, temperature set and efficiency of operator loading the belt.</i>		121 - 180 per hour
Shipping dimensions		
	main body	117 x 41 x 51"
	cooler & extension	81 x 41 x 57"
Shipping weight		
	main body	1000 lbs
	cooler & extension	500 lbs