

ELECTRIC DRYER MODELS: Features & Specs



SubliPro
2414

Product no. 71010

ELECTRIC DRYER MODELS	SubliPro 2414 9" Door Opening
product item number	71010
Features/Specs.	
Service Voltage	380V/415V 3-Ph
Amps per phase	26 Amps @ 380V 3-Ph 28 Amps @ 415V 3-Ph
KW / BTU @ 380V KW / BTU @ 415V	13.8 KW / 47,058 15.0 KW / 51,150 BTU
Unit Length Total	14' (427cm)
Unit Width Total	32" (81cm)
Oven Unit Height Total - to top of exhaust	67 1/2" (171.5cm)
Cooler Unit Height Total	74 1/4" (188.6cm)
Belt Width	24" (61cm)
Oven Length	60 Inches
"Dead" conveyor space between oven and cooler	12" (30.5cm)
Conveyor Entrance Length	24" (61cm)
Conveyor Exit Length	24" (61cm)
Fume Hood	6" (15cm) each end
Oven Throat / Door Openings	9" (22.8cm) With Curtains
Belt Speed Control	Digital
Belt Type	Stainless Steel
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Digital - West 6100
Number of Temp Control Zones	1 Zone
Relay Lights	Yes - 3
Heater Lights	Yes - 6
Recirculating Airflow	Yes - Variable
Number of Recirculating Air Zones	1 Zone
Recirculating Airflow speed	1500 CFM
Exhaust Duct Size	8" (20.3cm)
Exhaust CFM @ 60 Hz	350 CFM
Cooler Section	Yes
Cooler Length	3' (91cm)
CFM	1550
Wheels on Legs	Yes
Insulation under top skin	Yes
Certifications ETL/CE/CSA	CE
PRODUCTION CAPACITY PER HOUR:	
Mugs placed on 6" centers down the belt 4 wide on 24" belts, 6 wide on 36" belts and 7 wide on 48" belts with 12 minute retention time inside oven. <i>Note: Actual output will depend on ink requirement of retention time in the oven, temperature set and efficiency of operator loading the belt.</i>	120 - 180 per hour
Shipping dimensions	117 x 41 x 51"
main body	81 x 41 x 57"
cooler & extension	
Shipping weight	1000 lbs
main body	500 lbs
cooler & extension	