

ELECTRIC DRYER MODELS: Features & Specs



SubliPro
3626

Product no. 71055

ELECTRIC DRYER MODELS		SubliPro 3626 9" Opening 208V
product item number		71055
Features/Specs.		
Service Voltage		208V 3-Ph
Amps per phase		130 Amps 3-Ph
		3-Phase Only
KW / BTU input		42.0 KW / 143,220 BTU
Unit Length Total		26' (792cm)
Unit Width Total		44" (112cm)
Oven Unit Height Total - To top of exhaust		74" (188cm)
Cooler Unit Height Total		74" (188cm)
Belt Width		36" (91cm)
Oven Length		132 Inches
"Dead" conveyor space between oven and cooler		12" (30.5cm)
Conveyor Entrance Length		36 Inches
Conveyor Exit Length		36 Inches
Fume Hood		12" each end
Oven Throat / Door Openings		9" With Curtains
Belt Speed Control		Digital
Belt Type		Stainless Steel
Belt Direction Facing Control Box		Right to Left
Temperature Control - Type		Digital - West 6100
Number of Temp Control Zones		2 Zones
Relay Lights		Yes - 6
Heater Lights		Yes - 12
Recirculating Airflow		Yes - Variable
Number of Recirculating Air Zones		2 Zones
Recirculating Airflow speed		3000 CFM
Exhaust Duct Size		10"
Exhaust CFM @ 60 Hz		1000 CFM
Cooler Section		Yes
Cooler Length		6' (183cm)
CFM		4400
Wheels on Legs		Yes
Certifications ETL/CE/CSA		None
PRODUCTION CAPACITY PER HOUR Mugs placed on 6" centers down the belt 4 wide on 24" belts, 6 wide on 36" belts and 7 wide on 48" belts with 12 minute retention time inside oven. <i>Note: Actual output will depend on ink requirement of retention time in the oven, temperature set and efficiency of operator loading the belt.</i>		301 - 500 per hour
Shipping dimensions		
	main body	184 x 57 x 56"
	cooler & extension	130 x 57 x 56"
Shipping weight		
	main body	2400 lbs
	cooler & extension	1000 lbs