

ELECTRIC DRYER MODELS: Features & Specs



SubliPro
3626

Product no. 71004

ELECTRIC DRYER MODELS	SubliPro 3626 9" Door Opening
product item number	71004
Features/Specs.	
Service Voltage	380V/415V 3-Ph
Amps per phase	65 Amps @ 380V 3-Ph 70 Amps @ 415V 3-Ph
KW / BTU @ 380V KW / BTU @ 415V	40.8 KW / 139,128 BTU 44.4 KW / 151,404 BTU
Unit Length Total	26' (792cm)
Unit Width Total	44" (112cm)
Oven Unit Height Total - to top of exhaust	74" (188cm)
Cooler Unit Height Total	74" (188cm)
Belt Width	36" (91cm)
Oven Length	132 Inches
"Dead" conveyor space between oven and cooler	12" (30.5cm)
Conveyor Entrance Length	36" (91cm)
Conveyor Exit Length	36" (91cm)
Fume Hood	12" (30cm) each end
Oven Throat / Door Openings	9" (22.8cm)With Curtains
Belt Speed Control	Digital
Belt Type	Stainless Steel
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Digital - West 6100
Number of Temp Control Zones	2 Zones
Relay Lights	Yes - 6
Heater Lights	Yes - 12
Recirculating Airflow	Yes - Variable
Number of Recirculating Air Zones	2 Zones
Recirculating Airflow speed	3000 CFM
Exhaust Duct Size	10" (25.4cm)
Exhaust CFM @ 60 Hz	1000 CFM
Cooler Section	Yes
Cooler Length	6' (183cm)
CFM	4400
Wheels on Legs	Yes
Insulation under top skin	Yes
Certifications ETL/CE/CSA	CE
PRODUCTION CAPACITY PER HOUR:	
Mugs placed on 6" centers down the belt 4 wide on 24" belts, 6 wide on 36" belts and 7 wide on 48" belts with 12 minute retention time inside oven. <i>Note: Actual output will depend on ink requirement of retention time in the oven, temperature set and efficiency of operator loading the belt.</i>	300 - 500 per hour
Shipping dimensions	
main body	184 x 57 x 56"
cooler & extension	130 x 57 x 56"
Shipping weight	
main body	2400 lbs
cooler & extension	1000 lbs