

ELECTRIC DRYER MODELS: Features & Specs



NPII-1806

Product no. 36137

ELECTRIC DRYER MODELS	NPII-1806
product item number	36137
Features/Specs.	
Service Voltage	208-240V
	Single Phase Only
Amps per phase @ 240V	15 Amps 1-Ph 240V
KW / BTU @ 208 Volts	2.5 KW / 8,678 BTU
KW / BTU @ 220 Volts	2.8 KW / 9,708 BTU
KW / BTU @ 240 Volts	3.3 KW / 11,123 BTU
Power Cord Supplied?	Optional
Unit Length Total	6' (183cm)
Unit Width Total (body + control panel)	24" + 5" (61cm + 13cm)
Unit Height Total	47" (119cm)
Belt Width	18" (46cm)
Oven Length	42" (107cm)
Conveyor Entrance Length	15" (38cm)
Conveyor Exit Length	15" (38cm)
Fume Hood	None
Oven Throat / Door Openings	5" Adjustable
Belt Speed Control	Analog 0-10
Belt Type	Fiberglass TCF
Conveyor Pulleys	Flat
Belt Motor Outlets	N/A
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Digital - West 6100
Number of Temp Control Zones	1 Zone
High / Low Temp Alarm?	No
Relay Lights	Yes - 1
Heater Lights	Yes - 2
Heater Overload Protection	P&B W28 Series
Control Overload Protection	P&B W28 Series
Number of Heaters	2 - 18x18" 1631 watt
Recirculating Airflow	No
Number of Recirculating Air Zones	N/A
Recirculating Airflow speed	N/A
Exhaust Duct Size	4" - Side Mounted
Exhaust CFM @ 60 Hz	49 CFM
Exhaust Motor / Blade	1TDN8
Chimney None/Fixed/Variable	None
Backdraft Flapper?	None
Wheels on Legs	Optional
Insulation under top skin	Yes
Certifications ETL/CE/CSA	ETL / CSA
PRODUCTION CAPACITY PER HOUR (prints of 38 x 38cm occupying belt space of about 50 x 50cm, for 90 seconds and 60 seconds curing time - IN UNITS)	70 - 105
Shipping Weight (in kg and lbs)	167 kg - 370 lbs
Shipping size (in cm)	170 x 84 x 101 cm
Shipping size (in inches)	67 x 33 x 40"