

ELECTRIC DRYER MODELS: Features & Specs



NPII-3610

Product no. 70203

ELECTRIC DRYER MODELS	NPII-3610
product item number	70203
Features/Specs.	
Service Voltage	208-240V 3/1-Ph
Amps per phase @ 240V	27 Amps 3-Ph 47 Amps 1-Ph
KW / BTU @ 208 Volts	9.0 KW / 30,523 BTU
KW / BTU @ 220 Volts	10.0 KW / 34,147 BTU
KW / BTU @ 240 Volts	11.9 KW / 40,638 BTU
Power Cord Supplied?	No
Unit Length Total	10' (305cm)
Unit Width Total (body + control panel)	44" + 5" (112cm + 13cm)
Unit Height Total	47" (119cm)
Belt Width	36" (91cm)
Oven Length	60" (152cm)
Conveyor Entrance Length	30" (76cm)
Conveyor Exit Length	30" (76cm)
Fume Hood	None
Oven Throat / Door Openings	6" Adjustable
Belt Speed Control	Analog 0-10
Belt Type	Fiberglass TCF
Conveyor Pulleys	Flat
Belt Motor Outlets	N/A
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Digital - West 6100
Number of Temp Control Zones	1 Zone
High / Low Temp Alarm?	No
Relay Lights	Yes - 3
Heater Lights	Yes - 3
Heater Overload Protection	Snapax-Rocker
Control Overload Protection	Snapax-Rocker
Number of Heaters	3 - 12 x 36" 14.5 Ohm
Recirculating Airflow	Yes - Variable
Number of Recirculating Air Zones	1 Zone
Recirculating Airflow speed	1300 CFM
Exhaust Duct Size	3" Type B
Exhaust CFM @ 60 Hz	136 CFM
Exhaust Motor / Blade	4C941
Chimney None/Fixed/Variable	Fixed
Backdraft Flapper?	No
Wheels on Legs	Optional
Insulation under top skin	Yes
Certifications ETL/CE/CSA	ETL / CSA
PRODUCTION CAPACITY PER HOUR (prints of 38 x 38cm occupying belt space of about 50 x 50cm, for 90 seconds and 60 seconds curing time - IN UNITS)	223 - 334
Shipping Weight (in kg and lbs)	457 kg - 1015 lbs
Shipping size (in cm)	333 x 155 x 99cm
Shipping size (in inches)	131 x 61 x 39"