

ELECTRIC DRYER MODELS: Features & Specs



NPII-3616

Product no. 70270

ELECTRIC DRYER MODELS	NPII-3616
product item number	70270
Features/Specs.	
Service Voltage	208-240V 3/1-Ph
Amps per phase @ 240V	50 Amps 3-Ph 88 Amps 1-Ph
KW / BTU @ 208 Volts	15.3 KW / 52,069 BTU
KW / BTU @ 220 Volts	17.1 KW / 58,251 BTU
KW / BTU @ 240 Volts	20.3 KW / 69,323 BTU
Power Cord Supplied?	No
Unit Length Total	16' (488cm)
Unit Width Total (body + control panel)	44" + 5" (112cm + 13cm)
Unit Height Total	47" (119cm)
Belt Width	36" (91cm)
Oven Length	96" (244cm)
Conveyor Entrance Length	48" (122cm)
Conveyor Exit Length	48" (122cm)
Fume Hood	None
Oven Throat / Door Openings	6" Adjustable
Belt Speed Control	Analog 0-10
Belt Type	Fiberglass TCF
Conveyor Pulleys	Flat
Belt Motor Outlets	One
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Digital - West 6100
Number of Temp Control Zones	1 Zone
High / Low Temp Alarm?	No
Relay Lights	Yes - 6
Heater Lights	Yes - 6
Heater Overload Protection	Snapax-Rocker
Control Overload Protection	Snapax-Rocker
Number of Heaters	6 - 9x36" 170hm
Recirculating Airflow	Yes - Variable
Number of Recirculating Air Zones	1 Zone
Recirculating Airflow speed	2000 CFM
Exhaust Duct Size	4" Type B
Exhaust CFM @ 60 Hz	216 CFM
Exhaust Motor / Blade	4C942
Chimney None/Fixed/Variable	Fixed
Backdraft Flapper?	No
Wheels on Legs	Optional
Insulation under top skin	Yes
Certifications ETL/CE/CSA	ETL / CSA
PRODUCTION CAPACITY PER HOUR (prints of 38 x 38cm occupying belt space of about 50 x 50cm, for 90 seconds and 60 seconds curing time - IN UNITS)	357 - 535
Shipping Weight (in kg and lbs) Shipping size (in cm) Shipping size (in inches)	644 kg - 1431 lbs 333 x 158 x 112 cm 131 x 62 x 44"