

ELECTRIC DRYER MODELS: Features & Specs



NPII-3619

Product no. 70335

ELECTRIC DRYER MODELS	NPII-3619
product item number	70335
Features/Specs.	
Service Voltage	208-240V 3-Ph
Amps per phase @ 240V	70 Amps 3-Ph 3-Phase Only
KW / BTU @ 208 Volts	20.5 KW / 69,883 BTU
KW / BTU @ 220 Volts	22.9 KW / 78,179 BTU
KW / BTU @ 240 Volts	27.3 KW / 93,039 BTU
Power Cord Supplied?	No
Unit Length Total	19' (579cm)
Unit Width Total (body + control panel)	44" + 8" (112cm + 20cm)
Unit Height Total	47" (119cm)
Belt Width	36" (91cm)
Oven Length	132" (355cm)
Conveyor Entrance Length	48" (122cm)
Conveyor Exit Length	48" (122cm)
Fume Hood	None
Oven Throat / Door Openings	6" Adjustable
Belt Speed Control	Analog 0-10
Belt Type	Fiberglass TCF
Conveyor Pulleys	Flat
Belt Motor Outlets	One
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Digital - West 6100
Number of Temp Control Zones	2 Zones
High / Low Temp Alarm?	No
Relay Lights	Yes - 6
Heater Lights	Yes - 9
Heater Overload Protection	Snapax-Rocker
Control Overload Protection	Snapax-Rocker
Number of Heaters	9 - 9x36" 19 Ohm
Recirculating Airflow	Yes - Variable
Number of Recirculating Air Zones	2 Zones
Recirculating Airflow speed	4000 CFM
Exhaust Duct Size	5" Type B
Exhaust CFM @ 60 Hz	326 CFM
Exhaust Motor / Blade	4YJ33
Chimney None/Fixed/Variable	Fixed
Backdraft Flapper?	No
Wheels on Legs	Optional
Insulation under top skin	Yes
Certifications ETL/CE/CSA	ETL / CSA
PRODUCTION CAPACITY PER HOUR (prints of 38 x 38cm occupying belt space of about 50 x 50cm, for 90 seconds and 60 seconds curing time - IN UNITS)	490 - 735
Shipping Weight (in kg and lbs) Shipping size (in cm) Shipping size (in inches)	893 kg - 1985 lbs 421 x 162 x 122 cm 166 x 64 x 48"