

# ELECTRIC DRYER MODELS: Features & Specs



NPII-6019

Product no. CUSTOM

<b>ELECTRIC DRYER MODELS</b>	<b>NPII-6019</b>
<b>product item number</b>	<b>CUSTOM</b>
<b>Features/Specs.</b>	
Service Voltage	208-240V 3-ph
Amps per phase @ 240V	120 Amps 3-Ph 3-Phase Only
KW / BTU @ 208 Volts	34.6KW / 118,024 BTU
KW / BTU @ 220 Volts	38.7KW / 132,035 BTU
KW / BTU @ 240 Volts	46.1KW / 157,133 BTU
Power Cord Supplied?	No
Unit Length Total	19' (579cm)
Unit Width Total (body + control panel)	69" + 8" (175cm + 20cm)
Unit Height Total	47" (119cm)
Belt Width	60" (152cm)
Oven Length	132" (355cm)
Conveyor Entrance Length	48" (122cm)
Conveyor Exit Length	48" (122cm)
Fume Hood	12" each end
Oven Throat / Door Openings	6" Adjustable
Belt Speed Control	Analog 0-10
Belt Type	Fiberglass CG 9010
Conveyor Pulleys	Flat
Belt Motor Outlets	One
Belt Direction Facing Control Box	Right to Left
Temperature Control - Type	Digital - West 6100
Number of Temp Control Zones	2 Zones
High / Low Temp Alarm?	No
Relay Lights	Yes - 9
Heater Lights	Yes - 12
Heater Overload Protection	Snapax-Rocker
Control Overload Protection	Snapax-Rocker
Number of Heaters	12 - 12x30" 15 Ohm
Recirculating Airflow	Yes - Variable
Number of Recirculating Air Zones	2 Zones
Recirculating Airflow speed	4000 CFM
Exhaust Duct Size	5" Type B
Exhaust CFM @ 60 Hz	326 CFM
Exhaust Motor / Blade	4YJ33
Chimney None/Fixed/Variable	Fixed
Backdraft Flapper?	No
Wheels on Legs	Optional
Insulation under top skin	Yes
Certifications ETL/CE/CSA	ETL / CSA
PRODUCTION CAPACITY PER HOUR (prints of 38 x 38cm occupying belt space of about 50 x 50cm, for 90 seconds and 60 seconds curing time - IN UNITS)	817 - 1225
Shipping Weight (in kg and lbs) Shipping size (in cm) Shipping size (in inches)	1148 kg - 2550 lbs 470 x 203 x 122 cm 185 x 80 x 48"